



QC STL PRO-3.3X
QuietCool Stealth Pro Line

QC STL PRO-3.3X Specifications

Motor Voltage	120 VAC, 60 Hz	
Energy Use	Hi: 264 Watts / Low: 74.6 Watts	
Air Flow	Hi: 3159 CFM / Low: 1980 CFM	
HVI-916 Airflow (for CA Title 24 New Construction)	2350 CFM	
dBA	Hi: 47.4 / Low: 36.1	
Recommended SQFT Coverage @ 2 CFM per SQ FT	Covers 1053 SQFT to 1580 SQFT	
# of Speeds	2	
Duct Diameter	16"	
Duct Length	6 feet	
Motor Head Diameter	16 1/2"	
Motor Head Length	13 1/2"	
Dampers	Barometric Pressurized R5 Dampers	
Controls	Included 8 Hour Electronic Timer and HI-LOW-OFF Switch	
Warranty	15 Years	
Framing	None Required	
Joist Cutting	None Required; fits 16" or 24" on center	
Minimum Suggested Attic Venting	4.22 SQ FT net free area	
Ceiling Rough Opening	14 1/4" x 22 1/4"	
Removable Grille Outside Dimension	16" x 24"	
Shipping Weight	55 lbs.	
Box Dimensions	27" x 20" x 38"	
In The Box	<ul style="list-style-type: none"> -QC STL PRO-3.3X Motorhead -Removable Grille -Cut-out Template -Window Locks 	<ul style="list-style-type: none"> -Damper Box -6 Foot Duct -Accessory Bag -Controls



For more information, visit our website at:
QUIETCOOLSYSTEMS.COM